



XI'AN FUNCTION MATERIAL GROUP CO., LTD
Material Safety Data Sheet
Lithium Sulfide

1. Product and Company Identification

Trade Name: Lithium sulfide
Chemical Formula: Li_2S

Manufacturer/Supplier: XI'AN FUNCTION MATERIAL GROUP CO., LTD
Street: No. 69, Gazelle Valley, High-Tech Zone
City: XI'AN
State: Shaanxi
Zip Code: 710077
Country: China
Tel #: +86-29-88993870/+86-13519132051

2. Hazards Identification

Signal Word: Danger



Hazard Statements: H228 Flammable solid
H261 In contact with water, releases flammable gas
H301: Toxic if swallowed
H315 Causes skin irritation
H318 Causes serious eye damage
H335 May cause respiratory irritation

Precautionary Statements: P210 Keep away from heat/sparks/flame. No smoking.
P231+P232 Handle under inert gas
P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do—continue rinsing
P405: Store locked up
P501 Dispose of contents/container in accordance with local/regional/national/international regulations

HMIS Health Ratings (0-4):
Health: 3
Flammability: 2
Physical: 2

3. Composition

Chemical Family:	Salt
Additional Names:	None
Lithium sulfide (Li ₂ S):	
Percentage:	100 wt.%
CAS #:	12136-58-2
EC #:	235-228-1

4. First Aid Procedures

General Treatment:	Seek medical attention if symptoms persist.
Special Treatment:	None
Important Symptoms:	None
Inhalation:	Remove victim to fresh air. Supply oxygen if breathing is difficult.
Ingestion:	Seek medical attention.
Skin:	Wash affected area with mild soap and water. Remove any contaminated clothing.
Eyes:	Flush eyes with water, blinking often for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

5. Firefighting Measures

Flammability:	Flammable Reacts violently with water
Extinguishing Media:	Do not use water – use CO ₂ , sand, extinguishing powder.
Spec. Fire Fighting Procedure:	Use full-face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. See section 10 for decomposition products.

6. Accidental Release Measures

If Material Is Released/Spilled:	Wear appropriate respiratory and protective equipment specified in special protection information. Isolate spill area and provide ventilation. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for disposal. Take care not to raise dust.
Environmental Precautions:	Isolate runoff to prevent environmental pollution.

7. Handling and Storage

Handling Conditions:	Handle under dry protective gas. Wash thoroughly after handling.
Storage Conditions:	Store in a cool dry place in a tightly sealed container. Store under dry inert gas. Store apart from materials and conditions listed in section 10.
Work/Hygienic Maintenance:	Do not use tobacco or food in work area. Wash thoroughly before eating and smoking. Do not blow dust off clothing or skin with compressed air.
Ventilation:	Provide sufficient ventilation to maintain concentration at or below threshold limit.

8. Exposure Controls and Personal Protection

Permissible Exposure Limits:	None
Threshold Limit Value:	None
Special Equipment:	None
Respiratory Protection:	Dust Respirator
Protective Gloves:	Nitrile rubber, NBR 0.11mm thick.
Penetration time of glove material:	480 minutes
Eye Protection:	Safety glasses or goggles
Body Protection:	Protective work clothing. Wear close-toed shoes and long sleeves/pants.

9. Physical and Chemical Characteristics

Color	Yellow
Form:	Powder, Granules, Pellets, Sputtering target, Custom parts
Odor:	Rotten eggs
Water Solubility:	Reacts violently
Boiling Point:	1372 °C
Melting Point:	900-975 °C
Flash Point:	N/A
Autoignition Temperature:	N/A
Density:	1.66 g/cc
Molecular weight:	45.95 g/mol

10. Reactivity

Stability:	Stable under recommended storage conditions
Reacts with:	Reactions are violent with Water, Acids
Incompatible Conditions/Materials:	Acids, Water/Moisture
Hazardous Decomposition Products:	Hydrogen sulfide, Lithium oxide, Sulfur oxide

11. Toxicological Information

Potential Health Effects:	
Eyes:	Causes serious eye irritation
Skin:	causes skin irritation
Ingestion:	Toxic
Inhalation:	May cause irritation
Chronic:	N/A
Signs & Symptoms:	N/A
Aggravated Medical Conditions:	N/A
Median Lethal Dose:	1200 mg/kg to mouse by mouth 240 mg/kg to rat by mouth
Carcinogen:	N/A

12. Ecological Information

Aquatic Toxicity:	Low
Persistent Bioaccumulation Toxicity:	No
Very Persistent, Very Bioaccumulative:	No
Notes:	N/A


13. Disposal Considerations

Dispose of in accordance with local, state, national, and international regulations.

14. Transportation Data

Hazardous:

Hazardous for transportation.



Hazard Class:

8

Secondary Class

6.1 Toxic substances

Packing Group:

II

UN Number:

UN2923

Proper Shipping Name:

Water-reactive solid, toxic, n.o.s. (Lithium sulfide)

15. Regulatory Information

Sec 302 Extremely Hazardous:

No

Sec 304 Reportable Quantities:

N/A

Sec 313 Toxic Chemicals:

No

16. Other Information

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.

Document Last Revised:

07/28/2017